

Sit/Stand AV Lecterns

With Trolley



Model Number Structure

66 - SS

305730

LX

Series

Type

Size

Modesty Combination for

66=Lectern

SS= Sit/Stand Lectern
PS= Prestige Sit/ Stand
SSP=Sit/Stand Privacy

D x W x H

Laminate modesty
LX=Laminate modesty; No CPU shelf
LC=Laminate modesty panels & CPU shelf
Modesty Combination for Perforated

Metal modesty
MX=Metal modesty; No CPU shelf
MC=Metal modesty panels & CPU shelf



(217) 342-7070

www.novadesk.com

sales@novasolutionsinc.com

Sit/Stand AV Lecterns

1. Select model number

Ex: 66-SSP305730LX

(30x57x30 Sit/Stand Lectern with laminate modesty) **Select**

2. laminate color for base and worksurface


If ordering with perforated metal modesty, select metal color

Note: Laminate modesty will match base color.

Ex: 567 567
Base Worksurface

Optional Selections:

3. Select Visual Display Options (see page 34) Ex: TE0728NK (The Trolley™ EXL with NOVA keyboard drawer)




D x W x H (in.) ft³ / lbs Model

Laminate Modesty

30 x 58 ¾ x 30 39.8 / 360 66-SS305730LX

Perforated Metal Modesty (shown left)

30 x 58 ¾ x 30 39.8 / 360 66-SS305730MX



The Trolley™

- Ships installed in assembled units only.
- Maximum distance from center of wall mount VESA plate to bottom of monitor is 6 ¾" (171mm)

The Trolley™ E

Maximum Dimensions for Widescreen:

2 ½" D x 18 ¾" W x 14 ½" H up to 20" widescreen

The Trolley™ EXL

Maximum Dimensions for Widescreen:

2 ½" D x 22 ¾" W x 14 ½" H up to 24" widescreen 36" min. worksurface width

- Patented Access door automatically opens and closes with the push of a button
- Low voltage electrical motor to lift & lower monitor
- Intelligent Motion Technology™ provides operational intuition

Model Wt(lbs) Description

With NOVA Keyboard Drawer

NOVA Keyboard Drawer installed in assembled units only.

International Customers: The Trolley™ includes Universal Power Control Units, compatible with all power requirements inside and outside the U.S.

TE0724NK 48 Trolley™ E & NOVA Keyboard Drawer

TE0728NK 48 Trolley™ EXL & NOVA Keyboard Drawer

Available with  **NOVA Linked™** To order, see page 22.

Standard Features

- Electronically adjustable from base height of 30" with 12" of travel
- ADA compliant
- iMod™ wire management
- Powerstrip
- Lift capacity up to 550 lbs
- Column legs are standard black metal finish
- 12 RU rack rail storage in the right compartment (available with a rack cube)
- Laminate or metal modesty panel

Color Options

Base Color Options



WALNUT (537)



EMPIRE MAHOGANY (531)



WILD CHERRY (567)



FUSION MAPLE (560)



WHITE (664)



FASHION GREY (227)



SILVER (N99)



SLATE GREY (129)



BLACK (174)

Worksurface Color Options



BLACK LODESTONE (N62)



SILVER (N99)



FUSION MAPLE (560)



WILD CHERRY (567)



WALNUT (537)



FASHION GREY (227)



WHITE (664)



GRAPHITE NEBULA (030)



GREY NEBULA (044)



EMPIRE MAHOGANY (531)

Metallic Color Options (for Metal Modesty)



POLISHED BLACK (PBL)



POLISHED SILVER (PSL)



WHITE (WHT)




SLATE (SLL)


Options & Accessories

Factory Installed Accessories

Must specify location of grommet / power center at time of order

	Dimensions (in.)	Model
NOVA Keyboard Drawer 	Keyboard length to fit desk ordered. Only ordered when NO Visual Display Option is chosen 24" - 34" wide	NK
Rectangular Wire Grommet 	Rectangular black plastic grommet cover is removable for easy wire management 1 7/8" D x 3 1/4" W	WG1080
Star Cut Wire Grommet 	Round black plastic grommet with rubber star cut opening allows more cords and cables to pass through 2 3/4" Diameter	RWGSC
Pop-up Power Center 	Two grounded outlets. Fluid one touch accessibility. 6ft, 15 Amp cord. UL listed. 3 3/4" D x 5" W	11225PP
Pop-up Power / Data Center 	One grounded outlet. One opening for voice/data jack. Voice/Data Adapter Kit (included) provides adapters for couplers & jacks from a variety of manufacturers. Fluid one touch accessibility. 6ft, 15 Amp cord. UL listed. 3 3/4" D x 5" W	11225PD
Pop-up Power / USB Charging Center 	One grounded outlet. One USB charging duplex. Fluid one touch accessibility. 6ft, 15 Amp cord. UL Listed. 3 3/4" D x 5" W	11225PC
Round Flush Power Center 	Two grounded outlets. Clean, flush mount. 6ft, 15 Amp cord. UL listed. 4" Diameter	3359PP
Round Flush Power / USB Charging Center 	One grounded outlet. One USB charging duplex. Clean, flush mount. 6ft, 15 Amp cord. UL Listed. 4" Diameter	3359PC
Round Power Center 	One grounded outlet. Features spill-proof technology. 6ft, 15 Amp cord. UL Listed. 2" Diameter	3825P

Flip-up Shelf



D x W x H (in.)	ft ³ / lbs	Model	List Price
Field installed on all but Sit-Stand Lecterns. Shipped Separately. Color matches worksurface of lectern ordered. Located 3" down from worksurface. For factory prep, must specify "U" on lectern model number for left-handed, or "V" on lectern model number for right-handed placement, or "B" on lectern model number for both left and right hand placement.			


For 21" D or 24" D Lectern:

Attaches to the LEFT side panel of Lectern	20 x 20 x 1	0.9 / 24	66-SH202001L
Attaches to the RIGHT side panel of Lectern			

For 26" D, 30" D or 36" D Lectern:

Attaches to the LEFT side panel of Lecterns	22 x 20 x 1	1.0 / 24	66-SH222001L
Attaches to the RIGHT side panel of Lecterns	22 x 20 x 1	1.0 / 24	66-SH222001R

2 Space Rack Drawer




Attaches to rack rails. Takes up 2 RU space. 50 lb. weight capacity.			
20 x 15 x 3 ½	10.4 / 20	66-2DRAWER	

Sliding Shelf




Attaches to rack rails. 35 lb. weight capacity.			
20 x 15 x 1	10.4 / 15	66-SSHELF	

2 Space Rack Shelf



Attaches to rack rails. Takes up 2 RU space. 50 lb. weight capacity.			
20 x 15 x 3 ½	10.4 / 15	66-2SHELF	

Removable Console




Black laminate box (Customer to provide cutouts needed)			
11 x 15 x 6	2.0 / 20	66-CONSOLE01	

Ventilation Fan



115V fan rated at 57 CFM. 30 dBA. Add (-VF) on lectern model number to be factory installed. Must also specify cutout location on lectern.			
1 x 6 x 6	2.0 / 3	66-FAN	

Rack Cube



All metal construction providing front and rear Rack Rails allowing rack storage mounting prior to installation in rack storage compartment. Standard Black metal. Available with 6 RU - 14 RU; height varies by RU count. Complete Model number replacing blank " _ " with desired RU (Ex: 66-RRCUBE10 - 10 RU Rack Cube). NOTE: If ordering with a lectern, specify "-RR" at end of lectern model number. (Ex: 66-LP303047LM-RR)			
19 ⅛ x 19 ½ x Varies		66-RRCUBE_	