

# Sit/Stand AV Lecterns

## Privacy Sides With Locking CPU Door & Trolley



### Model Number Structure

66	-	SSP	306834	LD	TE0728NK
<u>Series</u>		<u>Type</u>	<u>Size</u>	<u>Modesty Combination for</u>	<u>Visual Display Option</u>
66=Lectern		SS= Sit/Stand Lectern PS= Prestige Sit/ Stand SSP=Sit/Stand Privacy	D x W x H	<p><b>Laminate modesty</b> LD=Laminate modesty panels &amp; CPU compartment with door</p> <p><b>Perforated Metal modesty</b> MD=Metal modesty &amp; CPU compartment with door</p>	<p>TE0724NK=Trolley™ E &amp; NOVA Keyboard Drawer</p> <p>TE0728NK=Trolley™ EXL &amp; NOVA Keyboard Drawer</p>



(217) 342-7070

www.novadesk.com

sales@novasolutionsinc.com

# Sit/Stand AV Lecterns

## 1. Select model number

Ex: 66-SSP306834LD  
(30x68x34 Sit/Stand Privacy Side Lectern with Locking CPU Door laminate modesty)

## 2. Select laminate color for base and worksurface


If ordering with perforated metal modesty, select metal color Note:

Laminate modesty will match base color.

Ex: 567     567  
Base     Worksurface

## Optional Selections:

3. Select Visual Display Options (see page 34) Ex: TE0728NK (The Trolley™ EXL with NOVA keyboard drawer)




D x W x H (in.)     ft<sup>3</sup> / lbs     Model

### Laminate Modesty

30 x 67<sup>7/16</sup> x 34     49.3 / 406     66-SSP306834LD

### Perforated Metal Modesty (shown left)

30 x 67<sup>7/16</sup> x 34     49.3 / 406     66-SSP306834MD



## The Trolley™

- Ships installed in assembled units only.
- Maximum distance from center of wall mount VESA plate to bottom of monitor is 6 3/4" (171mm)

### The Trolley™ E

Maximum Dimensions for Widescreen:

2 1/2" D x 18 3/8" W x 14 1/2" H up to 20" widescreen

### The Trolley™ EXL

Maximum Dimensions for Widescreen:

2 1/2" D x 22 3/8" W x 14 1/2" H up to 24" widescreen 36" min. worksurface width

- Patented Access door automatically opens and closes with the push of a button
- Low voltage electrical motor to lift & lower monitor
- Intelligent Motion Technology™ provides operational intuition

Model     Wt(lbs)     Description

### With NOVA Keyboard Drawer

NOVA Keyboard Drawer installed in assembled units only.

International Customers: The Trolley™ includes Universal Power Control Units, compatible with all power requirements inside and outside the U.S.

TE0724NK     48     Trolley™ E & NOVA Keyboard Drawer

TE0728NK     48     Trolley™ EXL & NOVA Keyboard Drawer

Available with  **NOVA Linked™** To order, see page 22.

## Standard Features

- Electronically adjustable from base height of 30" with 12" of travel
- ADA compliant
- iMod™ wire management
- Powerstrip
- Privacy Sides
- Locking CPU Door
- Lift capacity up to 550 lbs
- Column legs are standard black metal finish
- 12 RU rack rail storage in the right compartment (available with a rack cube)
- Laminate or metal modesty panel
- 8 1/2" CPU Storage

## Color Options

### Base Color Options



WALNUT (537)



EMPIRE MAHOGANY (531)



WILD CHERRY (567)



FUSION MAPLE (560)



WHITE (664)



FASHION GREY (227)



SILVER (N99)



SLATE GREY (129)



BLACK (174)

### Worksurface Color Options



BLACK LODESTONE (N62)



SILVER (N99)



FUSION MAPLE (560)



WILD CHERRY (567)



WALNUT (537)



FASHION GREY (227)



WHITE (664)



GRAPHITE NEBULA (030)



GREY NEBULA (044)



EMPIRE MAHOGANY (531)

### Metallic Color Options (for Metal Modesty)



POLISHED BLACK (PBL)



POLISHED SILVER (PSL)



WHITE (WHT)




SLATE (SLL)


# Options & Accessories

## Factory Installed Accessories

**Must specify location of grommet / power center at time of order**


	Dimensions (in.)	Model
<b>NOVA Keyboard Drawer</b> 	Keyboard length to fit desk ordered. Only ordered when NO Visual Display Option is chosen <b>24" - 34" wide</b>	<b>NK</b>
<b>Rectangular Wire Grommet</b> 	Rectangular black plastic grommet cover is removable for easy wire management <b>1 7/8" D x 3 1/4" W</b>	<b>WG1080</b>
<b>Star Cut Wire Grommet</b> 	Round black plastic grommet with rubber star cut opening allows more cords and cables to pass through <b>2 3/4" Diameter</b>	<b>RWGSC</b>
<b>Pop-up Power Center</b> 	Two grounded outlets. Fluid one touch accessibility. 6ft, 15 Amp cord. UL listed. <b>3 3/4" D x 5" W</b>	<b>11225PP</b>
<b>Pop-up Power / Data Center</b> 	One grounded outlet. One opening for voice/data jack. Voice/Data Adapter Kit (included) provides adapters for couplers & jacks from a variety of manufacturers. Fluid one touch accessibility. 6ft, 15 Amp cord. UL listed. <b>3 3/4" D x 5" W</b>	<b>11225PD</b>
<b>Pop-up Power / USB Charging Center</b> 	One grounded outlet. One USB charging duplex. Fluid one touch accessibility. 6ft, 15 Amp cord. UL Listed. <b>3 3/4" D x 5" W</b>	<b>11225PC</b>
<b>Round Flush Power Center</b> 	Two grounded outlets. Clean, flush mount. 6ft, 15 Amp cord. UL listed. <b>4" Diameter</b>	<b>3359PP</b>
<b>Round Flush Power / USB Charging Center</b> 	One grounded outlet. One USB charging duplex. Clean, flush mount. 6ft, 15 Amp cord. UL Listed. <b>4" Diameter</b>	<b>3359PC</b>
<b>Round Power Center</b> 	One grounded outlet. Features spill-proof technology. 6ft, 15 Amp cord. UL Listed. <b>2" Diameter</b>	<b>3825P</b>

### Flip-up Shelf




D x W x H (in.)	ft <sup>3</sup> / lbs	Model	List Price
<b>Field installed on all but Sit-Stand Lecterns. Shipped Separately. Color matches worksurface of lectern ordered. Located 3" down from worksurface. For factory prep, must specify "U" on lectern model number for left-handed, or "V" on lectern model number for right-handed placement, or "B" on lectern model number for both left and right hand placement.</b>			
<b>For 21" D or 24" D Lectern:</b>			
Attaches to the LEFT side panel of Lectern 20 x 20 x 1	0.9 / 24	<b>66-SH202001L</b>	
Attaches to the RIGHT side panel of Lectern			
<b>For 26" D, 30" D or 36" D Lectern:</b>			
Attaches to the LEFT side panel of Lecterns 22 x 20 x 1	1.0 / 24	<b>66-SH222001L</b>	
Attaches to the RIGHT side panel of Lecterns 22 x 20 x 1	1.0 / 24	<b>66-SH222001R</b>	

### 2 Space Rack Drawer




<b>Attaches to rack rails. Takes up 2 RU space. 50 lb. weight capacity.</b>			
<b>20 x 15 x 3 ½</b>	<b>10.4 / 20</b>	<b>66-2DRAWER</b>	

### Sliding Shelf




<b>Attaches to rack rails. 35 lb. weight capacity.</b>			
<b>20 x 15 x 1</b>	<b>10.4 / 15</b>	<b>66-SSHELF</b>	

### 2 Space Rack Shelf



<b>Attaches to rack rails. Takes up 2 RU space. 50 lb. weight capacity.</b>			
<b>20 x 15 x 3 ½</b>	<b>10.4 / 15</b>	<b>66-2SHELF</b>	

### Removable Console




<b>Black laminate box (Customer to provide cutouts needed)</b>			
<b>11 x 15 x 6</b>	<b>2.0 / 20</b>	<b>66-CONSOLE01</b>	

### Ventilation Fan



<b>115V fan rated at 57 CFM. 30 dBA. Add (-VF) on lectern model number to be factory installed. Must also specify cutout location on lectern.</b>			
<b>1 x 6 x 6</b>	<b>2.0 / 3</b>	<b>66-FAN</b>	

### Rack Cube



<b>All metal construction providing front and rear Rack Rails allowing rack storage mounting prior to installation in rack storage compartment. Standard Black metal. Available with 6 RU - 14 RU; height varies by RU count. Complete Model number replacing blank " _ " with desired RU (Ex: 66-RRCUBE10 - 10 RU Rack Cube). NOTE: If ordering with a lectern, specify "-RR" at end of lectern model number. (Ex: 66-LP303047LM-RR)</b>			
<b>19 ⅛ x 19 ½ x Varies</b>		<b>66-RRCUBE_</b>	