
# Standing Height Lecterns **Square Top**








## **Model Number Structure**





#### **Dimensions**

## 14 Rack Units / 2 Doors

Depth Options: 30" / 36"

Width Options: 30" / 36"

Height: 41"

#### 28 Rack Units / 2 Doors

Depth Options: 30" / 36"

Width Options: 42"


Height: 41"

## 28 Rack Units / 3 Doors

Depth Options: 30" / 36"

Width Options: 48"

Height: 41"




#### Includes/Features:


- 1" Thermofused Melamine
- Flat PVC Edge Banding
- Removable Locking Modesty Panels in Laminate or Perforated Metal
- Rack Rails
- Pull-out Shelf for Digital Presenters
- Flip-up Shelf (Optional)
- Wire Management
- Multi-plug Power Strips
- Locking Casters
- Locking Doors


LM = Laminate Modesty

Mm = Metal Modesty

Ships Assembled







## **Color Options**

### **Base Color Options**



(537)













(227)



(N99)





## Worksurface Color Options


























Laminate Modesty Panel

**Modesty Panel Options** 



Perforated Metal Modesty Panel

## Metallic Color Options (for Metal Modesty)







SLATE

#### Also Available with these Visual Display Options (Some Restrictions Apply)



Trolley™ Monitor Lift With the press of a button, the display emerges from its fully recessed compartment beneath the work surface while the patented access door provides a clean, uncluttered work space.



Downview<sup>TM</sup> The fully-adjustable arm allows for easy, under desk mounting of any flat panel display with all the benefits of the ergonomically proven Downward Gaze viewing angle.



**Articulating Surface Mount** Arm The Articulating Surface Arm

provides an adjustable and secure mounting solution for computer monitors



Surface Mount Arm The Surface Mount Arm attaches to the underside of the work surface and provides limited adjustability of the flat panel display.


# **Options & Accessories**

**Please Note:** All items on this page must be Field installed.

#### **Options for Standing Height Lecterns**

#### 2 Space Rack Drawer

Attaches to rack rails. Takes up 2 RU space. 50 lb. weight capacity





Flip-up shelf

Shipped Separately. Color matches worksurface of desk ordered. Located 3" down from worksurface.

Sizes available for all desks. See pricebook for model



Attaches to rack rails. 35 lb. weight capacity. Model Number: NK102024



2 Space Rack Shelf

Attaches to rack rails. Takes up 2 RU space . 50 lb. weight capacity. **Model Number: 66-2SHELF** 



#### Removable Console

Black laminate box. (Customer to provide cutouts needed). **Model Number: 66-CONSOLE01** 



Ventilation

115V fan rated at 57 CFM, 30 dBA, Factory installed in lectern - add (-VF) on lectern model number to be installed. Specify cutout location on lectern Model Number: 66-FAN



Fan

**Rack Cube** 

Available from 6 RU - 14 RU. Specify number of Rack Units at the end of model number. Standard Polished Black metal Model Number: 66-RRCUBE



#### Factory Installed Accessories

#### **Factory Installed NOVA Keyboard**



Keyboard length to fit desk ordered. Only ordered when NO Visual Display Option is chosen. Model Number: NK

#### **Rectangular Wire** Grommet

Rectangular black plastic grommet cover is removable for easy wire management.

Model Number: WG1080




One grounded outlet. 6Ft, 15 Amp cord. UL Listed Model Number: 1603N





Round black plastic grommet with rubber star cut opening allows more cords and cables to pass through.





Two grounded outlets. Fluid one touch accessibility.



6ft, 15 Amp cord. UL listed.

**Model Number: 11225PP** 

#### Pop-up Power/ Data Center



One grounded outlet. One opening for voice/data jack. Voice/Data Adapter Kit (included) provides adapters for couplers & jacks from a variety of manufacturers. Fluid one touch accessibility. 6ft, 15 Amp cord. UL listed. Model Number: 11225PD

#### Pop-up Power/ **USB** Charging Center

One grounded outlet. One USB charging duplex. Fluid one touch accessibility. 6ft, 15 Amp cord. UL Listed. Model Number: 11225PC



**Round Flush Power Center**  Two grounded outlets. Clean, flush mount. 6ft, 15 Amp cord. UL Listed



Model Number: 3359PP

**Round Flush** Power/USB Charging Center

One grounded outlet. One USB charging duplex. Clean, flush mount. 6ft, 15 Amp cord. UL Listed Model Number: 3359PC



